

19" Fibre Optic Patch Panels 1U – for 24 ports SC Simplex empty, black

CORNING

Part Number:
UU009631621

The patch panel range is designed as fibre optic patch panel mainly for backbone cable with pigtail splicing in splice cassettes, but can also be used for direct termination with e.g. the Hotmelt- or NPC connectors. Three types of panels allow the fixing of the backbone cable to 48 fibres through cable glands (16 and 20mm). The panel also offers fixing hooks for manifolds of pre terminated backbone cable. A central thread allows to stack up to 4 DIN splice cassettes incl. top lid. The cassette is secured against rotation. The panels have a sliding mechanism with a defined hard stop, which prevents the drawer from being pulled out completely and therefore offers the installer a comfortable handling for both, new installation and rearrangements. The optical panels program offers only panels without couplings.

Features and Benefits

Multiple labelling options

Port numbering above and below adapter modules or customised labels

Easy to remove top cover

No tools needed

Accomodate different termination methods

Pigtail splicing, field connectorisation, preterminated cables, Plug & Play™ or EDGE™ trunks can be installed in the same housing

Housing made of aluminium

Lightweight, but robust

LC Duplex adapter modules with self-closing shutters


Additional protection at no extra cost

Quick-mount feature

Allows single-person mounting of housing

Low installation depth

Mountable in shallow cabinets or racks



19" Fibre Optic Patch Panels 1U – for 24 ports SC Simplex empty, black



Specifications

Design - Adapter

Adapter type	SC simplex
--------------	------------

Design

Fibre count	24
Maximum Fibre Capacity	24
Convenient contractor-sized packaging length	2
Maximum number of fibers	12
Housing material	Aluminum
Cable entry type	Prepunched circular
Housing colour	Black
Number of panels per housing	1

General Specifications

Fibre category	SM - MM
Packaging	Box
Mounting Type	Rack 19"
Access type	Front, top, rear
Preconnectorized "Stubbed" hardware	No
Splice option	Yes

Dimensions

Height	436 mm
Width	483 mm
Depth	219 mm

19" Fibre Optic Patch Panels 1U – for 24 ports SC Simplex empty, black



Ordering Information

Product Number	UU009631621
Units per delivery	1/1

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.