

FREEDM™ B2 Tight Buffer Indoor/Outdoor Cable 24F G50 MMF ClearCurve® OM3 0.9mm TB3, B2ca-s1,d1,a1



CORNING

Part Number:
024T8X-32188E2C

Corning MPC (multipurpose cable) tight-buffered cables are flame-retardant, indoor/outdoor cables designed for interbuilding and intrabuilding backbones in duct and riser applications. The tight-buffered construction facilitates easier termination for low-fibre-count applications in the local area network (LAN) and eliminates need for fan-out kits. These cables are designed for installation in conduits, ducts and in-house.

Features and Benefits

Waterblocking technology

OSP (outdoor) applications

All-dielectric cable construction

Requires no grounding or bonding

UV- and microbe-resistant

Can be installed in ducts or conduits

Dry cable core by means of water swellable elements

Allows efficient and craft-friendly cable preparation in outdoor or indoor/outdoor applications

Small diameter and bend radius

Easy installation in space-constrained areas

TB3 tight-buffered construction

TB3 tight-buffered construction

Flame retardant

LSZH™/FRNC

Silicon-free outer jacket

The cable jacket and the outer jacket of subunits (not valid for 900 µm tight buffers) are free of harmful components to paint structures

FREEDM™ B2 Tight Buffer Indoor/Outdoor Cable 24F G50 MMF ClearCurve® OM3 0.9mm TB3, B2ca-s1,d1,a1



Specifications

Mechanical Specifications	
Crush resistance	500 N/10 cm
Min. bend radius installation	80 mm
Min. bend radius operation	67.5 mm
Nominal outer diameter	8.1 mm

Cable Design	
Cable marking	Metre - Handset - CE 17 EN 50575 B2ca-s1,d1,a1 - Sine - CORNING - Fiber Optic Cable - Year - FREEDM(TM) U-VQ(ZN)H 24 OM3CC TB3 0.9 LSZH(TM)/FRNC
Fibre count	24
Number of ripcords	1
Buffer tube diameter	900 mm
Outer jacket colour	Black
Buffering diameter	900 µm
Outer jacket material	Flame-retardant, non-corrosive/low-smoke, silicon-free, zero-halogen (FRNC/LSZH) material
Outer jacket nominal thickness	0.8 mm
Tensile strength elements and/or armouring - Layer 1	Aramid yarn
Tight buffer colour, layer 1	Blue, orange, green, brown, grey, white, red, black, yellow
Tight buffer colour, layer 2	Blue, orange, green, brown, grey, white, red, black, yellow, violet, pink, turquoise, violet, pink, turquoise
Tight buffer type	TB3 (easy strip up to 10 cm)
Flame rating	LSZH™/FRNC

General Specifications	
Environment	Indoor/Outdoor
Cable type	Tight-buffered
Product type	Dielectric

FREEDM™ B2 Tight Buffer Indoor/Outdoor Cable 24F G50 MMF ClearCurve® OM3 0.9mm TB3, B2ca-s1,d1,a1



General Specifications	
Fibre category	50 µm MM (OM3)
Application	Direct Buried, Duct, Vertical Riser, General Purpose Horizontal
Flame rating	LSZH™/FRNC
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-VQ(ZN)H

Dimensions	
Outer diameter	4.5 mm

Ordering Information	
Product Number	024T8X-32188E2C
Length	2000 m
Maximum delivery length	2000 m
Weight	22 kg
Weight	22 kg/km

Environmental Conditions	
Temperature range, installation	-5 °C to 50 °C
Temperature range, operation	-20 °C to 60 °C
Temperature range, storage	-25 °C to 70 °C

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Reaction to fire	B2ca, s1, d1, a1

Optical Characteristics	
Fibre code	T

FREEDM™ B2 Tight Buffer Indoor/Outdoor Cable 24F G50 MMF ClearCurve® OM3 0.9mm TB3, B2ca-s1,d1,a1

CORNING

Optical Characteristics

Fibre name	G50/125 ULTRA-BEND 7.5
Fibre Type	Multimode
Fibre core diameter	50 µm
Minimum effective modal bandwidth (EMB)	2000 MHz*km / -
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Min. overfilled launch (OFL) bandwidth	1500 MHz*km / 500 MHz*km
Serial 1 gigabit ethernet	1100 MHz*km / 600 MHz*km
Serial 10 gigabit ethernet	300 MHz*km/ 333 MHz*km
Typical attenuation	2.4 dB/km / 0.8 dB/km
Wavelengths	850 nm / 1300 nm
Induced Attenuation	For 7.5 mm radius < 0.2 db / -
Fibre category	OM3



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.