

MIC® Tight Buffer Indoor Cable 24F G50 MMF ClearCurve® OM4 0.9mm TB3, Cca-s1a,d1,a1



CORNING

Part Number:
024T8Z-32198E2G

Corning LANscape® indoor cables can be deployed indoor as building backbone (riser) cabling as well as for the cabling between floor distributors.

The tight-buffered construction facilitates easier termination for low-fiber-count applications in the local area network (LAN) and eliminates need for fan-out kits.

Features and Benefits

All-dielectric cable construction

Requires no grounding or bonding

Small diameter and bend radius

Easy installation in space-constrained areas

TB3 tight-buffered construction

Easy and consistent stripping over 10 cm

Silicon-free outer jacket

The cable jacket and the outer jacket of subunits (not valid for 900 µm tight buffers) are free of harmful components to paint structures

Flame retardant

LSZH™/FRNC

MIC® Tight Buffer Indoor Cable 24F G50 MMF ClearCurve® OM4 0.9mm TB3, Cca-s1a,d1,a1



Specifications

| Mechanical Specifications | |
|--|--------------|
| Crush resistance | 1000 N/10 cm |
| Fire load | 1.13 MJ/m |
| Max. tensile strength for installation | 1000 N |
| Min. bend radius installation | 120 mm |
| Min. bend radius operation | 80 mm |
| Nominal outer diameter | 8 mm |

| Cable Design | |
|--|---|
| Cable marking | Metre - Handset - CE 17 EN 50575 Cca-s1a,d1,a1 - Sine - CORNING - Fiber Optic Cable - Year - MIC(R) J-V(ZN)H 24 OM4CC TB3 0.9 LSZH(TM)/FRNC |
| Central element | Yarn |
| Fibre count | 24 |
| Number of ripcords | 1 |
| Buffer tube diameter | 900 mm |
| Outer jacket colour | Turquoise |
| Outer jacket material | Flame-retardant, non-corrosive/low-smoke, silicon-free, zero-halogen (FRNC/LSZH) material |
| Tensile strength elements and/or armouring - Layer 1 | Aramid yarn |
| Tight buffer type | TB3 (easy strip up to 10 cm) |
| Flame rating | LSZH™/FRNC |

| Environmental Conditions | |
|---------------------------------|-----------------|
| Temperature range, installation | -5 °C to 50 °C |
| Temperature range, storage | -25 °C to 70 °C |
| Temperature range, operation | -20 °C to 60 °C |

MIC® Tight Buffer Indoor Cable 24F G50 MMF ClearCurve® OM4 0.9mm TB3, Cca-s1a,d1,a1

CORNING

General Specifications

| | |
|---|--|
| Environment | Indoor |
| Cable type | Tight-buffered |
| Product type | Dielectric |
| Fibre category | 50 µm MM (OM4) |
| Flame rating | LSZH™/FRNC |
| Coding according to EN 60794-1-1 (DIN VDE 0888-100-1) | J-V(ZN)H |
| Application | Vertical Riser, General Purpose Horizontal, Indoor horizontal, General building applications |

Ordering Information

| | |
|-------------------------|-----------------|
| Product Number | 024T8Z-32198E2G |
| EAN Code | 4056418099514 |
| Maximum delivery length | 4000 m |
| Weight | 59 kg/km |

Standards

| | |
|-------------------------------|--|
| Reaction to fire | Cca, s1a, d1, a1 |
| RoHS | Free of hazardous substances according to RoHS 2011/65/EU |
| Flame Test Method | Flame retardant according to IEC 60332-1-2 (single cable) and IEC 60332-3-24 (bunch of cables) Reaction to fire according to EN 50575 and EN 13501-6 Low smoke according to IEC 61034 and zero halogen to IEC 60754-1 Non-corrosive according to IEC 60754-2 |
| Flame propagation test | Flame retardant according to IEC 60332-1-2 (single cable) and IEC 60332-3-24 (bunch of cables) |
| Reaction to fire requirements | Reaction to fire according to EN 50575 and EN 13501-6 |
| Smoke density | Low Smoke to IEC 61034 |
| Halogen content test | Zero Halogen to IEC 60754-1 |

MIC® Tight Buffer Indoor Cable 24F G50 MMF ClearCurve® OM4 0.9mm TB3, Cca-s1a,d1,a1



Standards

| | |
|--------------------|--|
| Level of corrosion | Non-corrosive according to IEC 60754-2 |
|--------------------|--|

Optical Characteristics

| | |
|---|--------------------------------|
| Fibre code | T |
| Fibre name | G50/125 ULTRA-BEND 7.5 |
| Fibre Type | Multimode |
| Fibre core diameter | 50 µm |
| Minimum effective modal bandwidth (EMB) | 4700 MHz*km / - |
| Maximum Attenuation | 2.8 dB/km / 1.0 dB/km |
| Min. overfilled launch (OFL) bandwidth | 3500 MHz*km / 500 MHz*km |
| Serial 1 gigabit ethernet | 1100 MHz*km / 600 MHz*km |
| Serial 10 gigabit ethernet | 550 MHz*km / - |
| Typical attenuation | 2.4 dB/km / 0.8 dB/km |
| Wavelengths | 850 nm / 1300 nm |
| Induced Attenuation | For 7.5 mm radius < 0.2 db / - |
| Fibre category | OM4 |



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.