

CCH Module Slack Storage Cassette, empty, for one CCH adapter panel

CORNING

Part Number: CCH-CF

CCH cassettes enable fast field termination and easy modular management of connectorization within the housing.

The CCH splicing cassette supports fusion splicing of individual or ribbon fibers, with heat shrinks, pigtail slack and cable slack managed within a single space saving footprint. This eliminates the need for individual splice trays or separate splice housings, as well as allowing splicing to be done away from the rack housing in a suitable workspace as needed. The modular design makes it easy to access the fiber in an individual cassette without disturbing the other fibers in the housing. A CCH panel with the desired adapter configuration can be ordered separately and fits easily into the cassette.

A CCH termination and slack storage cassette option with no splice tray, suitable for use with field-installable connectors, is also available.

Each cassette is shipped with one rail for use with CCH-01U/2U/3U housings and two rails used with CCH-04U and the WCH-02P/4P/6P housings. Grommets and cable ties for strain relief, and protective braided tubing for incoming cable are also included. Splicing cassettes ship with 12 single fiber heat-shrink splice protectors.

Features and Benefits

Manage cable slack for a CCH panel in a modular footprint

Fast, easy and reliable initial routing, and quick, simple reaccess for moves, adds and changes (MACs)

Splicing module holds 24 single fibre splices

Splice to full housing capacity, and manage all splices inside the housing

Includes everything needed to convert a CCH housing for modular routing and/or splicing

Easy ordering and field installation



CCH Module, Slack Storage Cassette, empty, for one CCH adapter panel

CCH Module Slack Storage Cassette, empty, for one CCH adapter panel

CORNING

Specifications

Design

Panel or module type	CCH
Housing type	Rack-Mountable Hardware

General Specifications

Mounting Type	Rack 19", Rack 23", Wall-mount
Product type	Rack-Mountable Hardware
Technology	Fusion Splice
Application	Data Centre, Enterprise Networks

Dimensions

Height	35 mm
Width	162 mm
Depth	200 mm

Ordering Information

Product Number	CCH-CF
EAN Code	4056418168913
Shipping weight	0.5 kg
Units per delivery	1/1

Environmental Conditions

Temperature range, operation	-40 °C to 70 °C
------------------------------	-----------------

CCH Module Slack Storage Cassette, empty, for one CCH adapter panel



Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	Meets ANSI/TIA/EIA-568A and 606



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.