

CCHE Panel, SC duplex UPC, 12 F, single-mode (OS2)

CORNING

Part Number: CCHE-CP12-72

The panels are used with field-installable connectors or in applications where the preconnectorized cables are routed directly from the equipment to the piece of inter-connect hardware. This provides an efficient way to securely mate two or more connectors.

Closet connector housing panels are offered in 6-, 8-, 12-, 16- and 24-fiber panels for use with the LANscape® solutions hardware products. The panels are used with field-installable connectors or in applications where the pre-connectorized cables are routed directly from the equipment to the inter-connect hardware. The panels are available with a variety of industry-standard adapter types. In most applications, the closet connector housing panels are designed for applications where specified labeling and connector identification are required. This is accomplished by the use of colored icons with different symbols molded into the icon.

Features and Benefits

Designed to accommodate all industry-standard adapter types

Unique colour-coded connector labeling system

Universal approach is used; one panel size fits in all standard LANscape Solutions hardware

Available in 6-, 8- and 12-fibre count options in most adapter styles; 16- and 24-fibre count options available in MT-RJ and LC duplex styles

Also available for copper modules 12-fibre ST Compatible Connector Panel, 12-fibre SC Duplex Panel, 24-fibre MT-RJ Connector Panel; 36-, 72- and 144-fibre count options available only with MTP adapters



CCHE Panel, SC duplex UPC, 12 F, single-mode (OS2)

CORNING

Specifications

Design - Adapter

Adapter housing colour	Blue
Adapter housing material	Composite
Keyed adapter	No
Shuttered adapter	No
Adapter type	SC duplex
Insert material	Ceramic

Design

Fibre count	12
Colour	Black
Number of adapters	6
Housing material	High-grade steel

General Specifications

Fibre category	Single-mode (OS2)
----------------	-------------------

Cable Design

Fibre count	12
-------------	----

Shipping Dimensions

Height	250 mm
Width	190 mm
Depth	180 mm

CCHE Panel, SC duplex UPC, 12 F, single-mode (OS2)

CORNING

Dimensions

Length	155 mm
Width	35 mm

Ordering Information

Product Number	CCHE-CP12-72
EAN Code	4042673761136
Weight	0.09 kg
Shipping weight	0.34 kg
Units per delivery	1/1

Environmental Conditions

Temperature range, operation	-20 °C to 70 °C
------------------------------	-----------------



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.