

# CCHE Panel, LC duplex 24 F, 50 µm multimode (OM3/OM4), shuttered

CORNING

## Part Number: CCHE-CP24-AD

The panels are used with field-installable connectors or in applications where the preconnectorized cables are routed directly from the equipment to the piece of inter-connect hardware. This provides an efficient way to securely mate two or more connectors.

Closet connector housing panels are offered in 6-, 8-, 12-, 16- and 24-fiber panels for use with the LANscape® solutions hardware products. The panels are used with field-installable connectors or in applications where the preconnectorized cables are routed directly from the equipment to the inter-connect hardware. The panels are available with a variety of industry-standard adapter types. In most applications, the closet connector housing panels are designed for applications where specified labeling and connector identification are required. This is accomplished by the use of colored icons with different symbols molded into the icon.

## Features and Benefits

Designed to accommodate all industry-standard adapter types

Unique colour-coded connector labeling system

Universal approach is used; one panel size fits in all standard LANscape Solutions hardware

Available in 6-, 8- and 12-fibre count options in most adapter styles; 16- and 24-fibre count options available in MT-RJ and LC duplex styles

Also available for copper modules 12-fibre ST Compatible Connector Panel, 12-fibre SC Duplex Panel, 24-fibre MT-RJ Connector Panel; 36-, 72- and 144-fibre count options available only with MTP adapters



# CCHE Panel, LC duplex 24 F, 50 µm multimode (OM3/OM4), shuttered



## Specifications

Design - Adapter	
Adapter housing colour	Turquoise
Adapter housing material	Composite
Keyed adapter	No
Shuttered adapter	Yes
Adapter type	LC duplex shuttered
Insert material	Ceramic

Design	
Fibre count	24
Colour	Black
Number of adapters	24
Housing material	High-grade steel

General Specifications	
Fibre category	50 µm MM (OM3/OM4)

Cable Design	
Fibre count	24

Shipping Dimensions	
Height	250 mm
Width	190 mm
Depth	180 mm

# CCHE Panel, LC duplex 24 F, 50 µm multimode (OM3/OM4), shuttered



## Dimensions

Length	155 mm
Width	35 mm

## Ordering Information

Product Number	CCHE-CP24-AD
EAN Code	4042673814481
Weight	0.08 kg
Shipping weight	0.3 kg
Units per delivery	1/1

## Environmental Conditions

Temperature range, operation	-20 °C to 70 °C
------------------------------	-----------------



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.