

# LANscape® Fibre Housing loaded with LC Duplex shuttered adapters and pigtails, 48 Fibres, 1U, Multimode OM3/OM4, universal splice pack, protectors not included, black

CORNING

**Part Number:**  
**LAN1-48AD-PGTL-B**

The LANscape® housing family was designed for various applications in 19-in racks and main distribution frames. The fixed or sliding housings can be equipped with industry common adapter types in different fiber categories and are suitable for direct field termination, fusion splicing with pigtails as well as preterminated solutions. The four back openings accommodate cable glands. Additional brackets for cable strain relief for FTTD/FTTO applications or U-Clips for Plug & Play™ and EDGE™ trunks can be mounted at the backside.

The space-optimized interior makes it easy to work with ongoing moves, adds and changes (MACs), thus reducing the risk of network disruptions.

## Features and Benefits

### Easy to remove top cover

No tools needed

### Housing made of aluminium

Lightweight, but robust

### Quick-mount feature

Allows single-person mounting of housing

### Accomodate different termination methods

Pigtail splicing, field connectorisation, preterminated cables, Plug & Play™ or EDGE™ trunks can be installed in the same housing

### Low installation depth


Mountable in shallow cabinets or racks

### Multiple labelling options

Port numbering above and below adapter modules or customised labels

### LC Duplex adapter modules with self-closing shutters

Additional protection at no extra cost



LANscape® Fibre Housing, loaded with LC Duplex shuttered adapters and pigtails, 48 Fibres, 1U, Multimode OM3/OM4, universal splice pack, protectors not included, black

# LANscape® Fibre Housing loaded with LC Duplex shuttered adapters and pigtails, 48 Fibres, 1U, Multimode OM3/OM4, universal splice pack, protectors not included, black

CORNING

## Specifications

### Design - Adapter

Adapter housing colour	Turquoise
Shuttered adapter	Yes
Adapter type	LC duplex shuttered

### Design

Fibre count	48
Splice tray type	Universal cassette with organisers for heat-shrink and crimp splice protectors
Housing material	Aluminum
Additional cable number reachable with accessories	4
Maximum cable number in basic unit with accessories	4
Cable entry type	Prepunched circular
Number of pigtails	48
Number of splice trays	4
Pigtail length	2 m
Splice protectors type	Without organizer and protectors
Number of adapters	24
Number of splice protectors	0
Total Splice Capacity	48 universal splices

### General Specifications

Fibre category	50 µm MM (OM3/OM4)
Access type	Front, top, rear
Lockable	Yes
Mounting Type	Rack 19"

**LANscape® Fibre Housing loaded with LC Duplex shuttered adapters and pigtails, 48 Fibres, 1U, Multimode OM3/OM4, universal splice pack, protectors not included, black**

CORNING

#### Cable Design

Fibre count	48
-------------	----

#### Dimensions

Height	44 mm
Width	483 mm
Depth	233 mm

#### Ordering Information

Product Number	LAN1-48AD-PGTL-B
Package contents	LANscape Fibre Housing with adapters, splice packs including coloured pigtails, 1x M20 cable gland and basic accessories
Units per delivery	1/1

#### Shipping Dimensions

Height	44 mm
Width	483 mm
Depth	233 mm



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.