FutureCom[™] Top hat rail adapter, LANscape® Grey

CORNING

Part Number: WAXISE-V0103-C001

The FutureCom[™] Industrial top hat rail adapter is suitable for installation on 35 mm top hat rails.

It provides a potential equalization spring and, due to its modular design, allows a free configuration of each single port with FutureCom copper modules as well as LANscape® fiber optic modules.

Features and Benefits

Compact design with small dimensions

Electrical spring contact to top hat rail (bonding, grounding)

Inclined design with labeling field and dust protection flap

Tool-less and fast installation on top hat rails

Tool-less installation of module

Top hat rail adapter light grey, RAL 7035

Flame retardant, fire Class UL94 V-0

Temperature range: -20°C to +70°C

Recyclable and free of heavy metal



FutureCom[™] Top hat rail adapter, LANscape® Grey

CORNING

Specifications

| Environmental Conditions | |
|---------------------------------|-----------------|
| Temperature range, installation | -20 °C to 70 °C |

| Design | |
|-----------------|------|
| Colour | Grey |
| Number of ports | 1 |

| General Specifications | | |
|------------------------|--------------|--|
| Product category | Core product | |
| Halogen-free | Yes | |

| Ordering Information | | |
|----------------------|-------------------|--|
| Product Number | WAXISE-V0103-C001 | |
| EAN Code | 4042673181972 | |
| Weight | 16 g | |
| Units per delivery | 1/1 | |

| Standards | |
|------------------|---|
| Flame retardance | Flame retardant, fire Class UL94 V-0 |
| RoHS | Free of hazardous substances according to RoHS 2011/65/EU |



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany +00 800 2675 4641 • FAX: +49 30 5303 2335 • <u>www.corning.com/opcomm/emea</u>

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.