

Conduit (Light Gauge) Product Data Sheet

Product Range	CR2, CR3 & CR4	<p>Image for reference only</p> 
Description	PVCu Round Conduit	
Key Features	<p>Light Gauge</p> <p>Range of Inspection Elbows, Bends & Tees</p> <p>Range of fittings</p> <p>Range of Round & Square boxes</p> <p>Operating Temperature -5°C to +60°C</p> <p>Non-Flame Propagating to BS EN 61386-1</p> <p>High Impact Resistance to -5°C Heavy Gauge Requirements of BS EN 61386-1</p>	
Dimensions	20mm, 25mm & 32mm	
Material(s)	PVCu (White and Black)	
Compliance / Standards(s)	<p>CE & UKCA Marked</p> <p>Low Voltage Directive 2014/35/EU</p> <p>The Electrical Equipment (Safety) Regulations 2016</p> <p>BS 7671:2018</p> <p>BS EN 61386-1:2008+A1:2019</p> <p>BS EN 60386-21:2004+A11;2010</p> <p>BS 4607-1:1984+A2:2010</p> <p>BS 4607-5:1982+A3:2010</p>	
Packaging	Recyclable	

Sustainability

We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Our PVC-U products are manufactured from an average of 80% recycled plastic, with some extruded products produced from 100% recycled material.

Conduit is manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.

- To find out more about the percentage of recycled material used in this product, please visit marshall-tufflex.com

