


Flush Mounted Dry Lining Boxes Product Data Sheet

| | | |
|---------------------------|---|--|
| Product Range | MDLB (See sheet 2 for more detail) | Image for reference only  |
| Description | Flush mounted Dry Lining Box for use within stud walls. | |
| Key Features | Wide securing outer flange. To suit board thickness from 1mm to 26mm Swivel snap out clamps Multiple Entry points Available with intumescent fire barrier pads | |
| Dimensions | See sheet 2 | |
| Material(s) | PVCu with Brass Inserts | |
| Compliance / Standards(s) | CE & UKCA Marked Low Voltage Directive 2014/35/EU The Electrical Equipment (Safety) Regulations 2016 BS 7671:2018 BS 5733:2010+A1:2014 BS 476-22:1987 when fitted with intumescent fire barrier pads | |
| Packaging | Recyclable | |

Sustainability

We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Our PVC-U products are manufactured from an average of 80% recycled plastic, with some extruded products produced from 100% recycled material.

Dry Lining Boxes are manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.

○ To find out more about the percentage of recycled material used in this product, please visit marshall-tufflex.com



| Stock Code | Single / Twin Gang | Depth (mm) | Adjustment (mm) |
|------------|--------------------|------------|-----------------|
| MDLB3WH | Single | 34 | 1-9 |
| MDLB1WH | Single | 34 | 6-14 |
| MDLB7WH | Single | 34 | 18-25 |
| MDLB4WH | Twin | 34 | 1-9 |
| MDLB2WH | Twin | 34 | 6-14 |
| MDLB8WH | Twin | 34 | 18-25 |
| MDLB22WH | Dual Single | 34 | 6-14 |
| MDLB13WH | Single | 25 | 1-9 |
| MDLB14WH | Twin | 25 | 1-9 |
| MDLB29WH | Single | 46 | 9-26 |
| MDLB30WH | Twin | 46 | 9-26 |

