

Faster – better – everywhere.





IT INFRASTRUCTURE SOFTWARE & SERVICES

DK 5302.052 Cable duct

State: 30/09/2022 (Source: rittal.com/uk-en)

POWER DISTRIBUTION

CLIMATE CONTROL



FRIEDHELM LOH GROUP

ENCLOSURES

DK 5302.052 - Cable duct for VX IT, TX CableNet, Data Rack

Cable duct with removable duct cover hinged on both sides.

Features

Model No.	DK 5302.052
Product description	Cable duct for concealed cable routing. Convenient access to the cabling at any time via the hinged duct cover, optionally removable. The duct has cable entry options to the enclosure interior and through the rear panel of the duct. The cable retaining bars enclosed with the duct are snap-mounted onto the cable fingers of the duct with variable depth to support cable routing. Alternatively, the cable duct may also be screw-fastened. For optimum air routing it may be combined with the brush kit for VX IT.
Benefits	Simple assembly with tool-free quick-release fastening High packing density due to U-based cable routing Suitable for back-to-back baying Cable duct may be used as a shielding element to prevent air short- circuits within cold aisle containment Lockable cable glands, may be fitted with installation components on the 1 U mounting standard
Material	Sheet steel Plastic to UL 94-HB
Colour	RAL 9005
Supply includes	Cable duct 2 covers 14 cable fingers , 6 U 10 cable retaining bars Assembly parts
Design	Cannot be combined with 482.6 mm (19") mounting angles, dynamic, for VX IT
Dimensions	Width: 109.5 mm Depth: 314.5 mm Length: 1,872 mm

Features

To fit	Enclosure type: VX IT
	Data Rack
	TX CableNet
	Width: = 800 mm
	Height: = 2,000 mm
	= 2,122 mm
Packs of	1 pc(s).
Weight/pack	8.56 kg
Copper weight (kg per piece)	0
Customs tariff number	39259020
EAN	4028177958586
ETIM 7.0	EC000012
ECLASS 8.0	27400703

Approvals

Approvals

GOST